

### Contractor Identification

#### NuGeneration Technologies, LLC

100 Professional Center Drive, Rohnert Park, CA 94928

(707) 820-4080 (For product information)

1-800-424-9300 or 1-202-483-7616 (CHEMTREC: For emergencies)

[www.nugentec.com](http://www.nugentec.com)

## CORROSION INHIBITOR -- WATER DISPLACING COMPOUND -- 6850-00-142-9389

### ==== Product Identification =====

Product ID: CORROSION INHIBITOR -- WATER DISPLACING COMPOUND

MSDS Date:03/21/2005

FSC:6850

MSDS Number: 142939

PN: NGT-142-9389

### ==== Composition/Information on Ingredients =====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 57%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:PROPANE/BUTANE

Fraction by Wt: 20%

ACGIH TLV:1000 PPM

Ingred Name:PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III)

CAS:127-18-4

RTECS #:KX3850000

Fraction by Wt: &lt;5%

OSHA PEL:100 PPM

ACGIH TLV:25PPM/100,A3 STEL;94

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:N-AMYL ACETATE (SARA III)

CAS:628-63-7

RTECS #:AJ1925000

Fraction by Wt: &lt;5%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:HEXYLENE GLYCOL

CAS:107-41-5

RTECS #:SA0810000

Fraction by Wt: 10%

OSHA PEL:C 25 PPM

ACGIH TLV:C 25 PPM; 9192

Ingred Name:KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Fraction by Wt: &lt;5%

ACGIH TLV:100 PPM

### ==== Hazards Identification =====

Health Hazards Acute and Chronic: PROLONGED INHALATION MAY CAUSE  
DIZZINESS AND NAUSEA. CAUSES SKIN AND EYE IRRITATION.

### ==== First Aid Measures =====

First Aid:INHALATION: REMOVE PATIENT TO FRESH AIR. TREAT AS CHLORINATED  
HYDROCARBON OVEREXPOSURE. SKIN: WASH THOROUGHLY WITH SOAP AND  
WATER. EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER, CONTACT PHYSICIAN.

===== Fire Fighting Measures =====

Unusual Fire/Explosion Hazard: DO NOT EXPOSE TO TEMPERATURES ABOVE 120 F.

===== Accidental Release Measures =====

Spill Release Procedures: COLLECT SPILL WITH ABSORBENT MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT EXPOSE TO DIRECT SUNLIGHT OR TO TEMPERATURES ABOVE 120 F.

===== Exposure Controls/Personal Protection =====

Ventilation: LOCAL EXHAUST  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V2  
Boiling Pt: B.P. Text:154F,68C  
Vapor Density:> THAN AIR  
Spec Gravity:1.216  
Evaporation Rate & Reference: SLOWER THAN ETHER  
Solubility in Water: NEGLIGIBLE  
Appearance and Odor: CLEAR, AMBER COLORED, SWEET SMELLING LIQUID.  
Percent Volatiles by Volume:100  
Corrosion Rate: NON-CORR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
Hazardous Decomposition Products: HYDROGEN CHLORIDE, CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL LAWS FOR CHLORINATED HYDROCARBONS.

**Disclaimer: NuGenTec provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. NUGENTEC MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, NUGENTEC WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.**