www.nugentec.com



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

1 Identification

- · Product Identifier
- · Trade name: AquaKlean STC-HT
- · Product Number: ng-AKSTCHT
- Relevant identified uses of the substance or mixture and uses advised against:

Highly alkaline, very low-foaming cleaner made for high pressure spray applications and agitated tank cleaning. Effective at low to very high temperatures. Product can either be rinsed post-cleaning or left on the surface; both of which provides superior flash-rust prevention on a wide variety of steel alloys. Avoid using on metals or metal alloys containing reactive metals such as Zinc, Aluminum, Lead or Tin.

- · Product Description Alkaline, non-foaming, rust-preventative detergent.
- · Details of the Supplier of the Safety Data Sheet:
- · Manufacturer/Supplier:

NuGeneration Technologies, LLC (dba NuGenTec) 1155 Park Avenue, Emeryville, CA 94608

salesteam@nugentec.com

1-888-996-8436 or 1-707-820-4080 for product information

· Emergency telephone number:

PERS Emergency Response: Domestic and Canada - 1-800-633-8253, International 1-801-629-0667

2 Hazard(s) Identification

· Classification of the substance or mixture:



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Aquatic Acute 2 H401 Toxic to aquatic life.

- · Hazard description: Mild
- Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

· Hazard pictograms:





GHS05 GHS07

· Signal word: Danger

· Hazard-determining components of labeling:

Potassium Hydroxide

Sodium Nitrite

Trade Secret

· Hazard statements:

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H401 Toxic to aquatic life.

Precautionary statements:

P260 Do not breathe dusts or mists.

P280 Wear eye protection / face protection.
 P273 Avoid release to the environment.
 P234 Keep only in original container.
 P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data

Sheet).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P390 Absorb spillage to prevent material damage.

P405 Store locked up.

P406 Store in corrosive resistant container with a resistant inner liner.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Unknown acute toxicity:

7 % of the mixture consists of component(s) of unknown toxicity.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



Health = 3 Fire = 0 Reactivity = 0

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

· HMIS-ratings (scale 0 - 4)



Health = 3Fire = 0

Reactivity = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

Non-hazardous components:				
527-07-1	Sodium Gluconate	5-10%		
7732-18-5	Water, distilled water, deionized water	60-90%		

- Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:				
CAS: 1310-58-3 RTECS: TT 2102000	Potassium Hydroxide ☐ C R35; Xn R22 → Skin Corr. 1A, H314; ↑ Acute Tox. 4, H302	15-35%		
CAS: 7632-00-0	Sodium Nitrite ☐ T R25; ☐ O R8; ☐ N R50 ⑤ Ox. Sol. 3, H272; ⑥ Acute Tox. 3, H301; ⑥ Aquatic Acute 1, H400	2-12%		
CAS: 111-46-6 RTECS: ID 5950000	Trade Secret	2-12%		

4 First-Aid Measures

- · Description of first aid measures:
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed:

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed: No further relevant information available.

— US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

5 Fire-Fighting Measures

- · Extinguishing media:
- Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture:

If incinerated, product will release teh following foxic fumes: Oxides of Carbon, Sodium, Potassium and Nitrogen (NOx).

- · Advice for firefighters:
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities:

Store away from strong acids, strong oxidizing agents, strong reducing agents, Ammonia, Cyanides, Amines, Activated Carbon, powdered metals, Alkali metals, reactive metals (Zinc, Aluminum, Lead, Tin) and their alloys, Nitro compounds, Halogens, Azides and Anhydrides.

- Storage
- · Requirements to be met by storerooms and receptacles: Store in the original container.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

· Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with occupational exposure limits:

1310-58-3 Potassium Hydroxide

REL Ceiling limit value: 2 mg/m³
TLV Ceiling limit value: 2 mg/m³

111-46-6 Trade Secret

WEEL Long-term value: 10 mg/m³

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

· Eye protection:



Tightly sealed goggles

· Body protection:



Protective work clothing

9 Physical and Chemical Properties

0 gram/liter

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Color: Yellow to light amber

· Odor: Mild

· Odor threshold: Not determined.

· pH-value @ 20 °C (68 °F): 13.5

13.2 5% b.v.

· Change in condition

Melting point/Melting range: Not determined.
Boiling point/Boiling range: 100 °C (212 °F)

· Flash point: None

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: 0.0 Vol % **Upper:** 0.0 Vol %

· Vapor pressure @ 20 °C (68 °F): 23 hPa (17 mm Hg)

• **Density @ 20 °C (68 °F):** 1.27 g/cm³ (10.598 lbs/gal)

Bulk density: 10.6 lbs/gal
 Relative density: Not determined.
 Vapor density: Not determined.
 Evaporation rate: Not determined.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

· Solubility in / Miscibility with:

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic @ **20** °**C** (**68** °**F**): 5 mPas

Kinematic: Not determined.

· Solvent content:

 Organic solvents:
 3.0 %

 Water:
 63.5 %

 VOC content:
 3.0 %

 Solids content:
 33.5 %

· Other information: No further relevant information available.

10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials:

Strong acids, strong oxidizing agents, strong reducing agents, Ammonia, Cyanides, Amines, Activated Carbon, powdered metals, Alkali metals, reactive metals (Zinc, Aluminum, Lead, Tin) and their alloys, Nitro compounds, Halogens, Azides and Anhydrides.

· Hazardous decomposition products: Oxides of Carbon, Sodium, Potassium and Nitrogen (NOx).

11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

LD/LC50	values that are	relevant for classification:
1310-58-3	Potassium Hy	droxide
Oral	LD50	273 mg/kg (rat)
7632-00-0	Sodium Nitrite	
Oral	LD50	175 mg/kg (mouse)
		157.9 mg/kg (rat)
Inhalative	LC50/96 hours	0.94-1.92 mg/l (Trout)
111-46-6	Trade Secret	
Oral	LD50	12565 mg/kg (rat)
Dermal	LD50	11890 mg/kg (rabbit)
		(Contd. on none

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

- · Primary irritant effect:
- · On the skin: Strong caustic effect on skin and mucous membranes.
- · On the eye:

Strong caustic effect.

Corrosive effect.

Causes serious eye irritation.

Additional toxicological information:

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

12 Ecological Information

- · Toxicity:
- · Aquatic toxicity:

7632-00-0 Sodium Nitrite

EC50 12.5 mg/l (Water flea)

- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes:

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 08/03/2016 Issue date 08/03/2016

Trade name: AquaKlean STC-HT

· Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings
- · Recommendation: Dispose of as unused product.

14 Transport Information

· UN-Number:

· DOT, ADR, IMDG, IATA

UN3266

· UN proper shipping name:

· DOT

· ADR

· IMDG, IATA

Corrosive liquid, basic, inorganic, n.o.s.

UN3266 Corrosive liquid, basic, inorganic, n.o.s. CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

· Transport hazard class(es):

· DOT



· Class: 8 Corrosive substances

· Label:

· ADR



· Class: 8 (C5) Corrosive substances

· Label:

· IMDG, IATA



· Class: 8 Corrosive substances

· Label:

· Packing group:

· DOT, ADR, IMDG, IATA

· Environmental hazards:

Not applicable.

8

(Contd. on page 10)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

· Special precautions for user: Warning: Corrosive substances

· Danger code (Kemler):

• EMS Number: F-A,S-B
• Segregation groups: Alkalis

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations:**On passenger aircraft/rail: 1 L
On cargo aircraft only: 30 L

· ADR

· Excepted quantities (EQ): Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· IMDG

· Limited quantities (LQ):

· Excepted quantities (EQ): Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN3266, Corrosive liquid, basic, inorganic, n.o.s., 8, II

15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- · SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

7632-00-0 Sodium Nitrite

· TSCA (Toxic Substances Control Act):

All ingredients are listed or exempt from listing.

- · California Proposition 65:
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

(Contd. on page 11)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

· Carcinogenic categories:

EPA (Environmental Protection Agency):

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





GHS05 GHS07

· Signal word: Danger

· Hazard-determining components of labeling:

Potassium Hydroxide

Sodium Nitrite

Trade Secret

· Hazard statements:

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H401 Toxic to aquatic life.

Precautionary statements:

P260 Do not breathe dusts or mists.
P280 Wear eye protection / face protection.

P273 Avoid release to the environment.
P234 Keep only in original container.
P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data

Sheet).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P390 Absorb spillage to prevent material damage.

P405 Store locked up.

(Contd. on page 12)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/03/2016 Reviewed on 08/03/2016

Trade name: AquaKlean STC-HT

P406 Store in corrosive resistant container with a resistant inner liner.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

Date of preparation / last revision: 08/03/2016 / -

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Ox. Sol. 3: Oxidizing solids - Category 3

Met. Corr.1: Corrosive to metals - Category 1

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

· * Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106