


OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Reviewed on 08/01/2016



Page 1/12





Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Reviewed on 08/01/2016

Trade name: Aquaklean EF145

P264	Wash thoroughly after handling.
P303+P361+P	353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
P304+P340	
P363	Wash contaminated clothing before reuse.
P301+P330+P	331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
· Unknown acu	te toxicity:
14.2 % of the n	nixture consists of component(s) of unknown toxicity.
 Classification 	system:
· NFPA ratings	(scale 0 - 4)
0 H Fi	$\begin{aligned} & ealth = 2 \\ & ire = 0 \\ & eactivity = 0 \end{aligned}$
· HMIS-ratings	(scale 0 - 4)
	Health = 2 Fire = 0 Reactivity = 0
· Hazard(s) not	otherwise classified (HNOC): None known

0.0				
3 Com	position/i	intormati	on on in	gredients

· Chemical	characterization:	Mixtures
------------	-------------------	-----------------

Description: Mixture: consisting of the following components

1310-73-2	Sodium Hydroxide	5-10%
	Skin Corr. 1A, H314	
	Proprietary Chelating Agent	1.5%
	🔶 Eye Dam. 1, H318; 🚸 Acute Tox. 4, H302	
	Proprietary Surfactant	1.2%
	🚸 Flam. Liq. 3, H226; 🔶 Eye Dam. 1, H318; 伙 Acute Tox. 4, H302	

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets. US

(Contd. on page 3)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Reviewed on 08/01/2016

Trade name: Aquaklean EF145

4 First-Aid Measures

- · Description of first aid measures:
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.
- · After eye contact: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention. · After swallowing:

Rinse out mouth and then drink plenty of water. Do not induce vomiting without medical advice. If vomiting does occur, repeat fluid administration Seek immediate medical advice.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed: No further relevant information available. · Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Fire-Fighting Measures

- · Extinguishing media:
- · Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · For safety reasons unsuitable extinguishing agents: Water with full jet

- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Advice for firefighters:
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Environmental precautions: Do not allow to enter sewers/surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. · Methods and material for containment and cleaning up: Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Trade name: Aquaklean EF145

Reviewed on 08/01/2016

Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Dispose of the collected material according to regulations.

 Reference to other sections: See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and Storage

· Handling

• **Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

- Conditions for safe storage, including any incompatibilities: Store away from strong acids, strong bases, strong oxidizing agents, strong reducing agents, light metals such as Aluminum or Zinc, and their alloys (Brass, etc.).
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

Components with occupational exposure limits:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1310-73-2 Sodium Hydroxide

- PEL Long-term value: 2 mg/m³
- REL Ceiling limit value: 2 mg/m³
- TLV Ceiling limit value: 2 mg/m³

· Additional information: The lists that were valid during the creation of this SDS were used as basis.

· Exposure controls:

- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

(Contd. on page 5)

US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Trade name: Aquaklean EF145

Reviewed on 08/01/2016

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing and wash before reuse. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

· Body protection:



Protective work clothing

9 Physical and Chemical Properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:	Liquid
Color:	Amber
· Odor:	Mild
· Odor threshold:	Not determined.
· pH-value @ 20 °C (68 °F):	12.7
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not determined. 100 °C (212 °F)

(Contd. on page 6)

US





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Trade name: Aquaklean EF145

Reviewed on 08/01/2016

Solids content: Other information:	24.5 % No further relevant information available.
Solvent content: Organic solvents: Water:	0.0 % 74.3 %
Viscosity: Dynamic @ 20 °C (68 °F): Kinematic:	1 mPas Not determined.
Partition coefficient (n-octanol/wate	er): Not determined.
Solubility in / Miscibility with: Water:	Not miscible or difficult to mix.
Density @ 20 °C (68 °F): Relative density: Vapor density: Evaporation rate:	1.167 g/cm³ (9.739 lbs/gal) Not determined. Not determined. Not determined.
Vapor pressure @ 20 °C (68 °F):	23 hPa (17 mm Hg)
Explosion limits: Lower: Upper:	Not determined. Not determined.
Danger of explosion:	Product does not present an explosion hazard.
Auto igniting:	Product is not self-igniting.
Decomposition temperature:	Not determined.
Ignition temperature:	Not determined.
Flammability (solid, gaseous):	Not applicable.
Flash point:	None

10 Stability and Reactivity

· Reactivity: No further relevant information available.

- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.

 Incompatible materials: Store away from strong acids, strong bases, strong oxidizing agents, strong reducing agents, light metals such as Aluminum or Zinc, and their alloys (Brass, etc.).

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Reviewed on 08/01/2016

Trade name: Aquaklean EF145

	nformation on toxicological effects: Acute toxicity:
	D/LC50 values that are relevant for classification:
1	310-73-2 Sodium Hydroxide
C	Dral LD50 2000 mg/kg (rat)
F	Proprietary Chelating Agent
C	Dral LD50 630-1260 mg/kg (rat)
· C · C · A · A · A · A	Primary irritant effect: On the skin: Strong caustic effect on skin and mucous membranes. On the eye: Strong irritant with the danger of severe eye injury. Corrosive effect. Causes serious eye irritation. Additional toxicological information: The product shows the following dangers according to internally approved calculation methods preparations: Corrosive rritant Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation esophagus and stomach.
· 1. 000 000 000 000 000 000 000 000 000 0	Carcinogenic categories: ARC (International Agency for Research on Cancer): Group 1 - Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 2B - Possibly carcinogenic to humans Group 3 - Not classifiable as to its carcinogenicity to humans Group 4 - Probably not carcinogenic to humans
	ITP (National Toxicology Program):
٨	lone of the ingredients are listed.
· (OSHA-Ca (Occupational Safety & Health Administration):
Λ	lone of the ingredients are listed.

· Toxicity:

· Aquatic toxicity:

1310-73-2 Sodium Hydroxide

EC50 40 mg/l (daphnia)

· Persistence and degradability: No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential: No further relevant information available.

(Contd. on page 8) -US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Reviewed on 08/01/2016

Trade name: Aquaklean EF145

- Mobility in soil: No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

· Other adverse effects: No further relevant information available.

13 Disposal Considerations

· Waste treatment methods:

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packagings
- · Recommendation:

Disposal must be made according to official regulations. Dispose of as unused product.

• Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport Information

- · UN-Number:
- · DOT, ADR, IMDG, IATA
- · UN proper shipping name:
- · DOT
- · ADR
- · IMDG, IATA
- · Transport hazard class(es):
- · DOT



· Class:

UN3266

Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide) UN3266 Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide) CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium Hydroxide)

8 Corrosive substances

(Contd. on page 9)

US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 08/01/2016 Issue date 08/01/2016 Trade name: Aquaklean EF145 · Label: 8 · ADR · Class: 8 (C5) Corrosive substances · Label: 8 · IMDG, IATA · Class: 8 Corrosive substances · Label: 8 · Packing group: · DOT, ADR, IMDG, IATA 1 Not applicable. · Environmental hazards: · Special precautions for user: Warning: Corrosive substances Danger code (Kemler): 88 · EMS Number: F-A,S-B · Segregation groups: Alkalis · Stowage Category В Stowage Code SW2 Clear of living guarters. - Segregation Code SG35 Stow "separated from" acids. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable. · Transport/Additional information: · DOT · Quantity limitations: On passenger aircraft/rail: 0.5 L On cargo aircraft only: 2.5 L · ADR · Excepted quantities (EQ): Code: E0 Not permitted as Excepted Quantity · IMDG · Limited quantities (LQ): 0 Code: E0 Excepted quantities (EQ): Not permitted as Excepted Quantity UN 3266 CORROSIVE LIQUID, BASIC, INORGANIC, · UN "Model Regulation": N.O.S. (SODIUM HYDROXIDE), 8, 1 us

(Contd. on page 10)



Reviewed on 08/01/2016



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Trade name: Aquaklean EF145

 Safety, health and environmental regulations/legislation specific for th SARA (Superfund Amendments and Reauthorization): 	e substance or mixture
· Section 355 (extremely hazardous substances):	
None of the ingredients are listed.	
· Section 313 (Specific toxic chemical listings):	
None of the ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed or exempt from listing.	
· California Proposition 65:	
· Chemicals known to cause cancer:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
· New Jersey Right-to-Know List:	
1310-73-2 Sodium Hydroxide	
New Jersey Special Hazardous Substance List:	
1310-73-2 Sodium Hydroxide	CO, F
· Pennsylvania Right-to-Know List:	
1310-73-2 Sodium Hydroxide	
Pennsylvania Special Hazardous Substance List:	
1310-73-2 Sodium Hydroxide	
· Carcinogenic categories:	
· EPA (Environmental Protection Agency):	
None of the ingredients are listed.	
• TLV (Threshold Limit Value established by ACGIH):	
None of the ingredients are listed.	
• NIOSH-Ca (National Institute for Occupational Safety and Health):	
None of the ingredients are listed.	
· GHS label elements	



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/01/2016

Reviewed on 08/01/2016

Page 11/12

Trade name: Aquaklean EF145 · Hazard pictograms: GHS05 · Signal word: Danger · Hazard-determining components of labeling: Sodium Hvdroxide Proprietary Chelating Agent Proprietary Surfactant · Hazard statements: H314 Causes severe skin burns and eye damage. · Precautionary statements: P260 Do not breathe dusts or mists. P280 Wear eye protection / face protection. P264 Wash thoroughly after handling. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P363 Wash contaminated clothing before reuse. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting. P405 Store locked up. Dispose of contents/container in accordance with local/regional/national/ P501 international regulations.

National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 08/01/2016 / -

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

(Contd. on page 12)

⁻US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Page 12/12

US

Issue date 08/01/2016

Trade name: Aquaklean EF145

Reviewed on 08/01/2016

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation - Category 1 • * Data compared to the previous version altered. SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106