

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

1 Identification

- **Product Identifier**
- **Trade name: DeSmut NS3**
- **Product Number: ng-DSNS3**
- **Relevant identified uses of the substance or mixture and uses advised against:**
Use as directed by manufacturer.
- **Product Description**
Etchant Solution for Stainless Steels, titanium, etc. and Aluminum desmut after etching.
- **Application of the substance / the mixture:** Industry-specific application.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
NuGeneration Technologies, LLC (dba NuGenTec)
1155 Park Avenue, Emeryville, CA 94608
salesteam@nugentec.com www.nugentec.com
1-888-996-8436 or 1-707-820-4080 for product information
- **Emergency telephone number:**
PERS Emergency Response: Domestic and Canada - 1-800-633-8253, International 1-801-629-0667

2 Hazard(s) Identification

- **Classification of the substance or mixture:**



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- **Label elements:**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS05 GHS07

- **Signal word: Danger**

- **Hazard-determining components of labeling:**

sulfuric acid

Nitric Acid

- **Hazard statements:**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3
Precautionary statements:

- P260 Do not breathe dusts or mists.
- P280 Wear eye protection / face protection.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P363 Wash contaminated clothing before reuse.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 0
Reactivity = 1

· **HMIS-ratings (scale 0 - 4)**



HEALTH 3 Health = 3
FIRE 0 Fire = 0
REACTIVITY 1 Reactivity = 1

· **Hazard(s) not otherwise classified (HNOC):** None known

3 Composition/Information on Ingredients

· **Chemical characterization:** Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

7664-93-9	sulfuric acid	⚠ Skin Corr. 1A, H314	15-35%
7697-37-2	Nitric Acid	⚠ Ox. Liq. 2, H272; ⚠ Skin Corr. 1A, H314	15-35%

· **Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

US

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

4 First-Aid Measures

- **Description of first aid measures:**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

- **After eye contact:**

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

- **After swallowing:**

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Do not induce vomiting without medical advice.

If vomiting does occur, repeat fluid administration

Seek immediate medical advice.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed:**

Ingestion: Can cause irritation and severe corrosive burns to mouth, throat, and stomach, and may be fatal if swallowed.

Inhalation: Gases or acid mist can cause severe irritation or corrosive burns to the upper respiratory system, including nose, mouth, and throat. Lung irritation, nitrogen oxide poisoning, and pulmonary edema can also occur. May cause severe breathing difficulties which may be delayed in onset.

Skin: Can cause severe corrosive burns or irritation. May stain the skin bright yellow.

Eyes: Can cause irritation, corneal burns, conjunctivitis, and may cause blindness. Contact lenses should not be worn when working with this material.

Summary of Chronic Health Hazards: Long-term exposure to concentrated vapors may cause erosion of teeth and lung damage. Long-term exposures seldom occur due to the corrosive properties of the acid.

- **Indication of any immediate medical attention and special treatment needed:**

Note to Physicians: Nitric Acid vapors contain nitrogen oxides. Acute overexposure by inhalation can result in delayed pulmonary edema. Observe affected patients for delayed effects up to 48 hours after exposure. Screen patients with chest x-ray, arterial blood gas, methemoglobinemia level, and pulmonary function tests. Bronchiolitis obliterans may develop weeks after exposure.

5 Fire-Fighting Measures

- **Extinguishing media:**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **Special hazards arising from the substance or mixture:** No further relevant information available.

(Contd. on page 4)

US

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

- **Advice for firefighters:**
- **Protective equipment:**
Mouth respiratory protective device.
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.
Avoid contact with skin, eyes and clothing.
Do not breathe vapor.
Keep people at a distance and stay upwind.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities:**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in the original container.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 5)

US

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

· **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· **Components with occupational exposure limits:**

7664-93-9 sulfuric acid

PEL	Long-term value: 1 mg/m ³
REL	Long-term value: 1 mg/m ³
TLV	Long-term value: 0.2* mg/m ³ *as thoracic fraction

7697-37-2 Nitric Acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



Suitable respiratory protective device recommended.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

US

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Color:

Colorless

· **Odor:**

Pungent

· **Odor threshold:**

Not determined.

· **pH-value @ 20 °C (68 °F):**

< 1

· **Change in condition**

Melting point/Melting range:

--

Boiling point/Boiling range:

83 °C (181 °F)

· **Flash point:**

None

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

Not determined.

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not self-igniting.

· **Danger of explosion:**

Product does not present an explosion hazard.

· **Explosion limits:**

Lower:

0.0 Vol %

Upper:

0.0 Vol %

· **Vapor pressure @ 20 °C (68 °F):**

23 hPa (17 mm Hg)

· **Density @ 20 °C (68 °F):**

1.266 g/cm³ (10.565 lbs/gal)

· **Relative density:**

Not determined.

· **Vapor density:**

Not determined.

· **Evaporation rate:**

Not determined.

(Contd. on page 7)

US

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

- **Solubility in / Miscibility with:**
 - Water:** Fully miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic @ 20 °C (68 °F):** 1.2 mPas
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 0.0 %
 - Water:** 60.5 %
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:**
Most metals, metallic powders, alcohol, charcoal, turpentine, hydrogen sulfide, wood excelsior, paper, cotton and similar organic materials. Alkalies, carbon, carbonates, cyanides, diborane organic chemicals, fluorine, phosphine, sulfides, thiocyanates. Nitric Acid is corrosive or incompatible with many common materials including mild steel, PVC, Viton®, and rubber.
Viton® is a registered trademark of DuPont Dow Elastomers.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects:**
 - **Acute toxicity:**
- | | | |
|---|---------------|------------------|
| LD/LC50 values that are relevant for classification: | | |
| 7664-93-9 sulfuric acid | | |
| Oral | LD50 Oral | 2140 ml/kg (rat) |
| Inhalative | LC50/96 hours | 375 mg/l (rat) |
| Sulfuric acid is harmful by all routes of entry. | | |
| 7697-37-2 Nitric Acid | | |
| Oral | LD50 | >90 mg/kg (rat) |
- **Primary irritant effect:**
 - **On the skin:** Strong caustic effect on skin and mucous membranes.
 - **On the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
Corrosive effect.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

Causes serious eye irritation.

· **Additional toxicological information:**

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories:**

· **IARC (International Agency for Research on Cancer):**

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

None of the ingredients are listed.

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

12 Ecological Information

· **Toxicity:**

· **Aquatic toxicity:**

7664-93-9 sulfuric acid

EC50 22 mg/l (daphnia)

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· **Results of PBT and vPvB assessment:**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

· **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

· **Waste treatment methods:**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Observe all federal, state and local environmental regulations when disposing of this material.

· **Uncleaned packagings**

· **Recommendation:**

Disposal must be made according to official regulations.

Dispose of as unused product.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport Information

· **UN-Number:**

· **DOT, ADR, IMDG, IATA**

UN3264

· **UN proper shipping name:**

· **DOT**

Corrosive liquid, acidic, inorganic, n.o.s.

· **ADR**

UN3264 Corrosive liquid, acidic, inorganic, n.o.s.

· **IMDG, IATA**

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

· **Transport hazard class(es):**

· **DOT**



· **Class:**

8 Corrosive substances

· **Label:**

8

· **ADR**



· **Class:**

8 (C1) Corrosive substances

· **Label:**

8

· **IMDG, IATA**



· **Class:**

8 Corrosive substances

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

- **Label:** 8
- **Packing group:** II
- **DOT, ADR, IMDG, IATA** II
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Warning: Corrosive substances
- **Danger code (Kemler):** 80
- **EMS Number:** F-A,S-B
- **Segregation groups:** Acids
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Hazardous substance:** 5000 lbs, 2270 kg

- **ADR**
- **Excepted quantities (EQ):** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **UN "Model Regulation":** UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S., 8, II

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

- **Section 355 (extremely hazardous substances):**

7664-93-9	sulfuric acid
7697-37-2	Nitric Acid

- **Section 313 (Specific toxic chemical listings):**

7664-93-9	sulfuric acid
7697-37-2	Nitric Acid

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed or exempt from listing.

- **California Proposition 65:**

- **Chemicals known to cause cancer:**

None of the ingredients are listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

· **New Jersey Right-to-Know List:**

7664-93-9	sulfuric acid
7697-37-2	Nitric Acid

· **New Jersey Special Hazardous Substance List:**

7664-93-9	sulfuric acid	CA, CO, R2
7697-37-2	Nitric Acid	CO, R2

· **Pennsylvania Right-to-Know List:**

7664-93-9	sulfuric acid
7697-37-2	Nitric Acid

· **Pennsylvania Special Hazardous Substance List:**

7664-93-9	sulfuric acid	E
7697-37-2	Nitric Acid	E

· **Carcinogenic categories:**

· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH):**

7664-93-9	sulfuric acid	A2
-----------	---------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS05 GHS07

· **Signal word: Danger**

· **Hazard-determining components of labeling:**

sulfuric acid
Nitric Acid

· **Hazard statements:**

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.

· **Precautionary statements:**

P260 Do not breathe dusts or mists.
P280 Wear eye protection / face protection.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 12)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/08/2016

Reviewed on 08/08/2016

Trade name: DeSmut NS3

P310	Immediately call a POISON CENTER/doctor.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P363	Wash contaminated clothing before reuse.
P301+P330+P331	If swallowed: Rinse mouth. Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Date of preparation / last revision:** 08/08/2016 / -

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Ox. Liq. 2: Oxidizing liquids – Category 2
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106