

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

1 Identification

- · Product identifier
- · Trade name: FluoSolv Flux Remover
- · Product number: -
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Product description Aerosol
- · Application of the substance / the mixture Aerosol spray flux remover
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

NuGeneration Technologies, LLC (dba NuGenTec)

1155 Park Ave, Emeryville, CA 94608

fluosolv@nugentec.com

For Product Info call 1-(800) 409-3142

www.fluosolv.com

www.nugentec.com/fluosolv

· Emergency telephone number:

PERS Emergency Response: Domestic and Canada - 1-800-633-8253, International 1-801-629-0667

2 Hazard(s) identification

· Classification of the substance or mixture



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Acute Tox. 4 H332 Harmful if inhaled.

Aguatic Chronic 3 H412 Harmful to aguatic life with long lasting effects.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

trans-dichloroethylene

Hazard statements

Harmful if swallowed or if inhaled.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

If swallowed: Call a poison center/doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Rinse mouth.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Unknown acute toxicity:
- 5 percent of the mixture consists of ingredient(s) of unknown toxicity.
- · Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 0 Reactivity = 1

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 0 Reactivity = 1

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/information on ingredients

Proprietary fluorinated fluid mixture

23%

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous Compone	ents:	
CAS: 156-60-5 RTECS: KV 9400000	trans-dichloroethylene Trans-dichloroethylene Trans-dichloroethylene Trans-dichloroethylene Trans-dichloroethylene Trans-dichloroethylene Trans-dichloroethylene Trans-dichloroethylene	Proprietary%
CAS: 124-38-9 RTECS: FF 6400000	Carbon Dioxide ♦ Press. Gas, H280; Simple Asphyxiant	<5%
CAS: 64-17-5	Ethyl alcohol † Flam. Liq. 2, H225; † Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	Proprietary%

4 First-aid measures

- · Description of first aid measures
- General information: Take affected persons out into the fresh air.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor: Treat symptomatically and supportively. No specific antidote.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

- · Most important symptoms and effects, both acute and delayed: Breathing difficulty
- Indication of any immediate medical attention and special treatment needed

Do not administer preparations of the adrenalin-ephedrine-group.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture
- Closed containers may explode when exposed to extreme heat.
- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

10



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

 Components with 	occupationa	l exposure limits:
-------------------------------------	-------------	--------------------

156-60-5 trans-dichloroethylene

PEL Long-term value: 790 mg/m³, 200 ppm REL Long-term value: 790 mg/m³, 200 ppm TLV Long-term value: 793 mg/m³, 200 ppm

124-38-9 Carbon Dioxide

PEL Long-term value: 9000 mg/m³, 5000 ppm

REL Short-term value: 54.000 mg/m³, 30.000 ppm

Long-term value: 9000 mg/m³, 5000 ppm

TLV Short-term value: 54.000 mg/m³, 30.000 ppm

Long-term value: 9000 mg/m³, 5000 ppm

64-17-5 Ethyl alcohol

PEL Long-term value: 1900 mg/m³, 1000 ppm REL Long-term value: 1900 mg/m³, 1000 ppm TLV Short-term value: 1880 mg/m³, 1000 ppm

Fluosolv Flux Remover (Calculated Allowable Exposure Limits)

AEL 375 ppm

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

(Contd. on page 5)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

· Eye protection:



Goggles recommended during refilling.

Information on basic physical and	chemical properties
General Information	
Appearance: Form:	Aerosol
Color:	Colorless
Odor:	Weak, characteristic
Odor threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	
Boiling point/Boiling range:	n/a °C (bulk liquid bp = 43 deg C)
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not applicable.
lgnition temperature:	440 °C (824 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	n/a
Upper:	n/a
Vapor pressure @ 20 °C (68 °F):	700 hPa (525 mm Hg)
Density:	
Relative density	1.29 g/l (bulk liquid density)
Vapor density	3.1 (Air=1)
Evaporation rate	<1 (Ether=1)
Solubility in / Miscibility with	
Water:	Max water in solvent = 100 ppm
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

· Solvent content:

VOC content: 72.0 % (775 g/l)

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity Stable under normal conditions
- · Chemical stability Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, flame and ignition sources.
- · Incompatible materials:

Avoid contact with Alkali metals and Alkaline earth metals, powdered metal salts, strong bases

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

156-60-5 trans-dichloroethylene

Oral LD50 770 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: No irritating effect.
- · on the eye: No irritating effect.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

- · **Toxicity** The hazards for the aquatic environment are unknown.
- Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	Not classified as dangerous in the meaning of transport regulations. DOT only - when shipped in packages with > 1470 lbs use: UN3082, Environmentally Hazardous Substance Liquid, N.O.S. (Dichloroethylene), 9, PGIII RO
DOT, ADR, IMDG, IATA	(Dichloroethylene) UN1950
UN proper shipping name	Aersols, Non-flammable
DOT	Aersols, Non-flammable
ADR	UN1950 Aerosols
IMDG	Aerosols, Marine Pollutant
IATA	AEROSOLS, non-flammable

110



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

· Transport hazard class(es) Not classified as dangerous in the meaning of transport

regulations.

DOT only - when shipped in packages with > 1470 lbs., use: UN3082, Environmentally Hazardous Substance, Liquid, N.O.S. (Dichloroethylene), 9, PGIII RQ

(Dichloroethylene)

· DOT



· Class 2 Gases · Label 2.2

· ADR



· Class 2 5A Gases · Label 2.2

· IMDG, IATA



2 Gases · Class · Label 2.2

· Packing group N/A

· DOT, ADR, IMDG, IATA Non-Regulated Material

· Environmental hazards: Not applicable.

· Special precautions for user

Warning: Gases Danger code (Kemler):

· EMS Number:

F-D,S-U

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

· ADR

Code: E0 · Excepted quantities (EQ)

Not permitted as Excepted Quantity

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

· IMDG · Limited quantities (LQ) 1L

• Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN1950, Aerosols, 2.2

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · California Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

64-17-5 Ethyl alcohol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

156-60-5 trans-dichloroethylene

| | | | |

· TLV (Threshold Limit Value established by ACGIH)

64-17-5 Ethyl alcohol

*A*3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

· Signal word Warning

Hazard-determining components of labeling:

trans-dichloroethylene

Hazard statements

Harmful if swallowed or if inhaled.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

If swallowed: Call a poison center/doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Rinse mouth.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· State Right to Know

All ingredients are listed.

· Other regulations, limitations and prohibitive regulations

CERCLA Reportable Quantity: 1470 lbs, based on the percentage composition of this chemical in the product.:

trans-Dichloroethylene

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision 06/23/2015 / -

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/23/2015 Reviewed on 06/23/2015

Trade name: FluoSolv Flux Remover

vPvB: very Persistent and very Bioaccumulative VPVB: very Persistent and very Bioaccumulative
Press. Gas: Gases under pressure: Compressed gas
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

* Potencial Province of the Province Paragraph of the Province Paragraph of the Province Paragraph of the Paragr

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106