www.nugentec.com



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

1 Identification

· Product identifier

Trade name: Grease Cutter 2
 Product number: ngt-GPR712

· CAS Number: mixture

· Relevant identified uses of the substance or mixture and uses advised against

· Product description PC35 Washing and cleaning products (including solvent based products)

· Application of the substance / the mixture High Caustic Cleaner and Degreaser

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

NuGeneration Technologies, LLC (dba NuGenTec)

1155 Park Avenue, Emeryville, CA 94608

salesteam@nugentec.com

888-996-8436 or 707-820-4080 for product information

· Emergency telephone number:

PERS Emergency Response: Domestic and Canada - 1-800-633-8253, International 1-801-629-0667

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

Sodium Hydroxide

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

Wear eye protection / face protection.

Wash thoroughly after handling.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

Trade name: Grease Cutter 2

Immediately call a poison center/doctor.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash contaminated clothing before reuse.

If swallowed: Rinse mouth. Do NOT induce vomiting.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Unknown acute toxicity:
 - 12 percent of the mixture consists of ingredient(s) of unknown toxicity.
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 4Fire = 0Reactivity = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/information on ingredients			
CAS: 1300-72-7	Sodium Xylene Sulfonate	5-10%	
CAS: 68603-25-8	Ethoxylated Propoxylated C8-C10 Alcohols Skin Irrit. 2, H315; Eye Irrit. 2B, H320	2-12%	
CAS: 7732-18-5 RTECS: ZC 0110000	water, distilled, conductivity or of similar purity	60-90%	

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous Compone	ents:	
	ANIONIC SURFACTANT • Skin Irrit. 2, H315	15-35%
CAS: 1310-73-2	Sodium Hydroxide Skin Corr. 1A, H314	2-12%
CAS: 111-76-2 RTECS: KJ 8575000	Ethylene Glycol Monobutyl Ether Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Flam. Liq. 4, H227	2-12%
CAS: 60-00-4 RTECS: AH 4375000	edetic acid © Eye Irrit. 2A, H319	≤2.5%

- US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

Trade name: Grease Cutter 2

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed:

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:
- CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

Trade name: Grease Cutter 2

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:

1310-73-2 Sodium Hydroxide

PEL Long-term value: 2 mg/m³
REL Ceiling limit value: 2 mg/m³
TLV Ceiling limit value: 2 mg/m³

111-76-2 Ethylene Glycol Monobutyl Ether

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 97 mg/m³, 20 ppm

BEI[°]

· Ingredients with biological limit values:

111-76-2 Ethylene Glycol Monobutyl Ether

BEI 200 mg/g creatinine

urine

end of shift

Butoxyacetic acid with hydrolysis

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

Trade name: Grease Cutter 2

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Light yellow
Odor: Light

· Odor threshold: Not determined.

· pH-value @ 20 °C (68 °F): 13.5

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:Not determined.
100 °C (212 °F)Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Ignition temperature:240 °C (464 °F)Decomposition temperature:Not determined.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

Trade name: Grease Cutter 2

· **Auto igniting:** Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: 0.0 Vol % **Upper:** 0.0 Vol %

· **Vapor pressure** @ **20 °C (68 °F)**: 23 hPa (17 mm Hg)

• Density @ 20 °C (68 °F): 1.11 g/cm³ (9.263 lbs/gal)

Relative density @ 20 °C (68 °F)
 Vapor density
 Evaporation rate
 9.5 lb/gal
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

• Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

 Organic solvents:
 5.0 %

 Water:
 62.0 %

 VOC content:
 5.0 %

 Solids content:
 5.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

1310-73-2 Sodium Hydroxide

Oral LD50 2000 mg/kg (rat)

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

Trade name: Grease Cutter 2

111-76-2	Ethylene (Glycol Monobutyl Ether
Oral	LD50	470 mg/kg (rat)
Dermal	LD50	220 mg/kg (rab)
Inhalative	LC50/4 h	2174.91 mg/l (rat)
60-00-4 ed	detic acid	
Oral	LD50	4500 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong irritant with the danger of severe eye injury.

Corrosive effect.

Causes serious eye irritation.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (II	nternation	nal Agen	icy for R	Research d	on Cancer)

111-76-2 Ethylene Glycol Monobutyl Ether

3

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

111-76-2 Ethylene Glycol Monobutyl Ether

EC50 1815 mg/l (Water flea)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/14/2015 Issue date 05/14/2015

Trade name: Grease Cutter 2

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA
- · UN proper shipping name
- · DOT
- · ADR
- · IMDG, IATA
- · Transport hazard class(es)
- · DOT



· Class

· Label

· ADR



· Class

· Label

· IMDG, IATA



· Class

UN1760

Corrosive liquids, n.o.s. (Sodium Hydroxide) UN1760 Corrosive liquids, n.o.s. (Sodium Hydroxide) CORROSIVE LIQUID, N.O.S. (Sodium Hydroxide)

8 Corrosive substances

8 (C5) Corrosive substances

8 Corrosive substances

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

Trade name: Grease Cutter 2

· Label 8

· Packing group

· DOT, ADR, IMDG, IATA |||

• Environmental hazards: Not applicable.

· Special precautions for user Warning: Corrosive substances

Danger code (Kemler): 88
EMS Number: F-A,S-B
Segregation groups Alkalis

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations** On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

· ADR

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

• UN "Model Regulation": UN1760, Corrosive liquids, n.o.s. (Sodium Hydroxide), 8,

III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 Ethylene Glycol Monobutyl Ether

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · California Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

(Contd. on page 10)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

Trade name: Grease Cutter 2

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

111-76-2 Ethylene Glycol Monobutyl Ether

NL

· TLV (Threshold Limit Value established by ACGIH)

111-76-2 Ethylene Glycol Monobutyl Ether

А3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS05

· Signal word Danger

Hazard-determining components of labeling:

Sodium Hydroxide

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

Wear eve protection / face protection.

Wash thoroughly after handling.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash contaminated clothing before reuse.

If swallowed: Rinse mouth. Do NOT induce vomiting.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

State Right to Know

CAS: 7732-18-5 water, distilled, conductivity or of similar purity RTECS: ZC 0110000

60-90%

(Contd. on page 11)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/14/2015 Reviewed on 05/14/2015

Trade name: Grease Cutter 2

	ANIONIC SURFACTANT	15-35%
	♦ Skin Irrit. 2, H315	
CAS: 1300-72-7	Sodium Xylene Sulfonate	5-10%
CAS: 68603-25-8	Ethoxylated Propoxylated C8-C10 Alcohols	2-12%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2B, H320	
CAS: 111-76-2	Ethylene Glycol Monobutyl Ether	2-12%
RTECS: KJ 8575000	① Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Flam. Liq. 4, H227	
CAS: 1310-73-2	Sodium Hydroxide	2-12%
	🔷 Skin Corr. 1A, H314	
All ingredients are list	ed.	

[·] Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision 05/14/2015 / 1

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

· * Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106