

\*

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

### Issue date 11/02/2015

Reviewed on 11/02/2015

i i oudot idollar	ier	
	er: ngt-scw402 ified uses of the substance or mixture	e and uses advised against: oducts (including solvent based products)
<ul> <li>Manufacturer/S NuGeneration T 1155 Park Aven salesteam@nug</li> </ul>	echnologies, LLC (dba NuGenTec) ue, Emeryville, CA 94608	www.nugentec.c
· Emergency tele	ephone number:	-800-633-8253, International 1-801-629-066
2 Hazard(s) Ide		
· Classification o	of the substance or mixture:	
GHS0	8 Health hazard	
Asp. Tox. 1	H304 May be fatal if swallowed and	enters airways.
GHS0	9 Environment	
Aquatic Acute 1	H400 Very toxic to aquatic life.	
Aquatic Chronic	1 H410 Very toxic to aquatic life with le	ong lasting effects.
<b>^</b>	7	
GHS0		
GHS0 Skin Irrit. 2	H315 Causes skin irritation.	
Skin Irrit. 2 Eye Irrit. 2A	H319 Causes serious eye irritation.	
Skin Irrit. 2 Eye Irrit. 2A Skin Sens. 1	H319 Causes serious eye irritation. H317 May cause an allergic skin rea	
Skin Irrit. 2 Eye Irrit. 2A	H319 Causes serious eye irritation.	
Skin Irrit. 2 Eye Irrit. 2A Skin Sens. 1	H319 Causes serious eye irritation. H317 May cause an allergic skin rea	



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Trade name: Tar-Off

Reviewed on 11/02/2015

· Hazard pictograms: GHS08 GHS09 GHS07 · Signal word: Danger · Hazard-determining components of labeling: d-limonene Distillates (petroleum), hydrotreated light · Hazard statements: Combustible liquid. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. · Precautionary statements: Keep away from flames and hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves / eye protection / face protection. Wear protective gloves. Wear eye protection / face protection. Avoid release to the environment. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). IF SWALLOWED: Immediately call a POISON CENTER/ doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Do NOT induce vomiting. In case of fire: Use for extinction: CO2, powder or water spray. IF ON SKIN: Wash with plenty of water. Collect spillage. Take off contaminated clothing and wash it before reuse. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Trade name: Tar-Off · Classification system: NFPA ratings (scale 0 - 4) Health = 1Fire = 2Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 12 Fire = 2FIRE Reactivity = 0REACTIVITY 0 · Hazard(s) not otherwise classified (HNOC): None known

o competition/m	formation on Ingredients	
ANION	IC SURFACTANT	15-35%
🚸 Skii	Irrit. 2, H315	
68603-25-8 ethoxy	ated propoxylated c8-c10 alcohols	15-35%
🚸 Skii	Irrit. 2, H315; Eye Irrit. 2A, H319	
• Dangerous Compo CAS: 5989-27-5	d-limonene	25-50%
	<ul> <li>Aquatic Acute 1, H400; Aquatic Chronic 1, H410; (1) Skin Irrit. 2, H315; Skin Sens. 1, H317; Flam. Liq. 4, H227</li> </ul>	20-0070
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Askin Irrit. 2, H315; STOT SE 3, H336; Flam. Liq. 4, H227	25-50%

## 4 First-Aid Measures

- · Description of first aid measures:
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:
- Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.
- · After eye contact:
- Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed:* No further relevant information available.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Page 4/13

#### Trade name: Tar-Off

• Indication of any immediate medical attention and special treatment needed: No further relevant information available.

### 5 Fire-Fighting Measures

- · Extinguishing media:
- · Suitable extinguishing agents:
- CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. **Special hazards arising from the substance or mixture:**

Combustible liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above flashpoint.

- · Advice for firefighters:
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

### 6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures: Not required.
- · Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Dispose of the collected material according to regulations.

 Reference to other sections: See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

## 7 Handling and Storage

- · Handling
- Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: Protect from heat.
- · Conditions for safe storage, including any incompatibilities:
- · Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- No further relevant information available.. Protect from heat and direct sunlight.

(Contd. on page 5)

US





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Trade name: Tar-Off

· Specific end use(s): No further relevant information available.

## 8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters:
- · Components with occupational exposure limits:
- 5989-27-5 d-limonene

TWA Short-term value: 10 mg/m<sup>3</sup>

64742-47-8 Distillates (petroleum), hydrotreated light

OSHA PEL Long-term value: 5 mg/m<sup>3</sup>

· Additional information: The lists that were valid during the creation of this SDS were used as basis.

### · Exposure controls:

- · Personal protective equipment:
- · General protective and hygienic measures:
- The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material:** The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.
- Eye protection:



Tightly sealed goggles

(Contd. on page 6)

US



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Trade name: Tar-Off

Information on basic physical and General Information	chemical properties
Appearance: Form: Color: Odor: Odor threshold:	Liquid Colorless Vinegar Not determined.
pH-value @ 20 °C (68 °F):	12
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Not determined. 173 °C (343 °F)
Flash point:	68 °C (154 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	210 °C (410 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Not determined.
Explosion limits: Lower: Upper:	0.5 Vol % 6.5 Vol %
Vapor pressure @ 20 °C (68 °F):	2.3 hPa (2 mm Hg)
Density @ 20 °C (68 °F): Relative density: Vapor density: Evaporation rate:	1.071 g/cm³ (8.937 lbs/gal) Not determined. Not determined. Not determined.
Solubility in / Miscibility with: Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity: Dynamic @ 20 °C (68 °F): Kinematic:	10 mPas Not determined.
Solvent content: Organic solvents: VOC content: Other information:	70.0 % 70.0 % No further relevant information available.

(Contd. on page 7)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Trade name: Tar-Off

## 10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

		les that are relevant for classification:	
5989-2	7-5 d-li	imonene	
Oral	LD50	4400 mg/kg (rat) Remarks: Behavioral: Change in motor activity (specific assay). Respiratory dis Skin and Appendages: Other: Hair	sorde
Derma	I LD50	>5000 mg/kg (rabbit)	
64742-		istillates (petroleum), hydrotreated light	
Oral		>5000 mg/kg (rat)	
Dermal	I LD50	>2000 mg/kg (rabbit)	
On the Irritant May ca On the Sensit	skin: to skin use an eye: In ization:	nt effect: and mucous membranes. allergic skin reaction. rritating effect. : Sensitization possible through skin contact.	
On the Irritant May ca On the Sensiti Addition The pro- prepara Irritant Carcin	skin: to skin a use an eye: In ization: onal to oduct s ations: ogenic	and mucous membranes. allergic skin reaction. rritating effect. : Sensitization possible through skin contact. <b>xicological information:</b> shows the following dangers according to internally approved calculation metho shows the following dangers according to internally approved calculation metho <b>categories:</b>	ods :
On the Irritant May ca On the Sensiti Addition The pro- prepara Irritant Carcin IARC (1	skin: to skin a eye: In ization: onal to oduct s ations: ogenic Interna	and mucous membranes. allergic skin reaction. rritating effect. : Sensitization possible through skin contact. <b>xicological information:</b> shows the following dangers according to internally approved calculation metho shows the following dangers according to internally approved calculation metho categories: ational Agency for Research on Cancer):	
On the Irritant May ca On the Sensiti Addition The pro- prepara Irritant Carcin IARC (1	skin: to skin a eye: In ization: onal to oduct s ations: ogenic Interna	and mucous membranes. allergic skin reaction. rritating effect. : Sensitization possible through skin contact. <b>xicological information:</b> shows the following dangers according to internally approved calculation metho shows the following dangers according to internally approved calculation metho <b>categories:</b>	ods
On the Irritant May ca On the Sensiti Addition The pro- prepara Irritant Carcin IARC (1 5989-2	skin: to skin a use an eye: Ir ization: onal to oduct s ations: ogenic Interna 7-5 d-li	and mucous membranes. allergic skin reaction. rritating effect. : Sensitization possible through skin contact. <b>xicological information:</b> shows the following dangers according to internally approved calculation metho shows the following dangers according to internally approved calculation metho categories: ational Agency for Research on Cancer):	ods

(Contd. on page 8)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Trade name: Tar-Off

Ecologic	al Information
Toxicity:	
Aquatic to	cicity:
Avoid relea	se into the environment. Runoff from fire control or dilution water may cause pollution.
5989-27-5 0	1-limonene
EC50 0.36	mg/l (daphnia) (OECD Test Guideline 202)
64742-47-8	Distillates (petroleum), hydrotreated light
EC50 25 m	g/l (Trout) (OECD Test Guideline 203, 96 hour, Static Test)
	e and degradability: No further relevant information available.
	n environmental systems:
	<i>Ilative potential:</i> No further relevant information available.
	soil: No further relevant information available.
Ecotoxical	effects:
Remark: Vo	ery toxic for fish
Additional	ecological information:
General no	tes:
	v product to reach ground water, water course or sewage system.
	Irinking water if even small quantities leak into the ground.
	for fish and plankton in water bodies.
	or aquatic organisms
	bigger amounts into drains or the aquatic environment may lead to increased pH-values.
	lue harms aquatic organisms. In the dilution of the use-level the pH-value is considerab
	that after the use of the product the aqueous waste, emptied into drains, is only low wate
dangerous.	
	PBT and vPvB assessment:
PBT: Not a	
vPvB: Not a	
Other adve	rse effects: No further relevant information available.

## **13 Disposal Considerations**

- · Waste treatment methods:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

## 14 Transport Information

- · UN-Number:
- · DOT

· ADR, IMDG, IATA

Non-Regulated Material UN3082

(Contd. on page 9)

US



US



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015 Reviewed on 11/02/2015 Trade name: Tar-Off · UN proper shipping name: · DOT Non-Regulated Material · ADR UN3082 Environmentally hazardous substances, liquid, n.o.s. (Dipentene, Distillates (petroleum), hydrotreated light) · IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIPENTENE, Distillates (petroleum), hydrotreated light), MARINE POLLUTANT ·IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIPENTENE, Distillates (petroleum), hydrotreated light) Transport hazard class(es): · DOT · Class: Non-Regulated Material · ADR · Class: 9 (M6) Miscellaneous dangerous substances and articles 9 · Label: · IMDG, IATA · Class: 9 Miscellaneous dangerous substances and articles · Label: 9 · Packing group: · DOT Non-Regulated Material · ADR. IMDG. IATA 111 · Environmental hazards: Product contains environmentally hazardous substances: d-limonene, Distillates (petroleum), hydrotreated light · Special marking (ADR): Symbol (fish and tree) · Special marking (IATA): Symbol (fish and tree) · Special precautions for user: Warning: Miscellaneous dangerous substances and articles · Danger code (Kemler): 90 · EMS Number: F-A,S-F Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable. (Contd. on page 10)





Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Transport/Additional information:	
ADR	
Excepted quantities (EQ):	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ):	5L
Excepted quantities (EQ):	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCES, LIQUID, N.O.S. (DIPENTENE DISTILLATES (PETROLEUM), HYDROTREATE LIGHT), 9, III
Safety, health and environmental SARA (Superfund Amendments a	,
Regulatory Information Safety, health and environmental SARA (Superfund Amendments a Section 355 (extremely hazardous None of the ingredients are listed.	nd Reauthorization):
Safety, health and environmental SARA (Superfund Amendments a Section 355 (extremely hazardous	nd Reauthorization):
Safety, health and environmental SARA (Superfund Amendments a Section 355 (extremely hazardous None of the ingredients are listed.	nd Reauthorization):
Safety, health and environmental SARA (Superfund Amendments a Section 355 (extremely hazardous None of the ingredients are listed. Section 313 (Specific toxic chemic	nd Reauthorization): s substances): cal listings):
Safety, health and environmental SARA (Superfund Amendments a Section 355 (extremely hazardous None of the ingredients are listed. Section 313 (Specific toxic chemic None of the ingredients are listed.	nd Reauthorization): s substances): cal listings):

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories:

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

(Contd. on page 11)

US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Trade name: Ta	ar-Off
----------------	--------

- GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms:



- · Signal word: Danger
- · Hazard-determining components of labeling: d-limonene Distillates (petroleum), hydrotreated light · Hazard statements: Combustible liquid. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. · Precautionary statements: Keep away from flames and hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves / eye protection / face protection. Wear protective gloves. Wear eye protection / face protection. Avoid release to the environment. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). IF SWALLOWED: Immediately call a POISON CENTER/ doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Do NOT induce vomiting. In case of fire: Use for extinction: CO2, powder or water spray. IF ON SKIN: Wash with plenty of water. Collect spillage. Take off contaminated clothing and wash it before reuse. Store locked up. Store in a well-ventilated place. Keep container tightly closed. (Contd. on page 12)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Trade name: Tar-Off

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### · National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

<ul> <li>State Right to Know:</li> </ul>		
CAS: 5989-27-5	d-limonene	25-50%
RTECS: GW 6360000	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; (1) Skin Irrit. 2, H315; Skin Sens. 1, H317; Flam. Liq. 4, H227	
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	25-50%
	Asp. Tox. 1, H304; H315; STOT SE 3, H336; Flam. Liq. 4, H227	
	ANIONIC SURFACTANT	15-35%
	🚸 Skin Irrit. 2, H315	
CAS: 68603-25-8	ethoxylated propoxylated c8-c10 alcohols	15-35%
	🚸 Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
All ingredients are liste	d.	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other Information**

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 11/02/2015 / 1

#### · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 4: Flammable liquids, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Asp. Tox. 1: Aspiration hazard, Hazard Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1 (Contd. on page 13)

\_\_\_\_\_US

Page 12/13



US



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2015

Reviewed on 11/02/2015

Trade name: Tar-Off

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

\* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106