www.nugentec.com



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

1 Identification

- · Product Identifier
- · Trade name: Truck Wash Plus
- · Product Number: ngt-gpr655b
- · Relevant identified uses of the substance or mixture and uses advised against:

Industrial Strength – Car and truck wash

- · Product Description PC35 Washing and cleaning products (including solvent based products)
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier:

NuGeneration Technologies, LLC (dba NuGenTec)

1155 Park Avenue, Emeryville, CA 94608

salesteam@nugentec.com

1-888-996-8436 or 1-707-820-4080 for product information

· Emergency telephone number:

PERS Emergency Response: Domestic and Canada - 1-800-633-8253, International 1-801-629-0667

2 Hazard(s) Identification

· Classification of the substance or mixture:



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS05

· Signal word: Danger

· Hazard-determining components of labeling:

Sodium Metasilicate Pentahydrate

Sodium Hydroxide

· Hazard statements:

H314 Causes severe skin burns and eye damage.

· Precautionary statements:

P260 Do not breathe dusts or mists. P280 Wear eye protection / face protection. P264 Wash thoroughly after handling.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data

Sheet).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Unknown acute toxicity:

14.5 % of the mixture consists of component(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 4Fire = 0Reactivity = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

· Non-hazardous components:

7732-18-5 Water, distilled water, deionized water

60-90%

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

Dangerous Compone	ents:	
CAS: 25155-30-0	Sodium dodecylbenzenesulphonate	15-35%
CAS: 111-76-2 RTECS: KJ 8575000	Ethylene Glycol Monobutyl Ether Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Flam. Liq. 4, H227	2-12%
CAS: 10213-79-3	Sodium Metasilicate Pentahydrate Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; STOT SE 3, H335	2-12%
	ANIONIC SURFACTANT Skin Irrit. 2, H315	2-12%
CAS: 1310-73-2	Sodium Hydroxide Skin Corr. 1A, H314	≤2.5%
CAS: 60-00-4 RTECS: AH 4375000	Edetic acid © Eye Irrit. 2A, H319	≤2.5%

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

- · Description of first aid measures:
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed:

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

- · Extinguishing media:
- Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Advice for firefighters:
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Dilute with plenty of water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

Dispose of the collected material according to regulations.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities:
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-76-2 Ethylene Glycol Monobutyl Ether

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 97 mg/m³, 20 ppm

BEI

1310-73-2 Sodium Hydroxide

PEL | Long-term value: 2 mg/m³

REL Ceiling limit value: 2 mg/m³

TLV Ceiling limit value: 2 mg/m3

· Ingredients with biological limit values:

111-76-2 Ethylene Glycol Monobutyl Ether

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

BEI 200 mg/g creatinine

urine

end of shift

Butoxyacetic acid with hydrolysis

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Blue
• Odor: Mild Odor

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

· Odor threshold: Not determined.

· pH-value @ 20 °C (68 °F): 13.7

· Change in condition

Melting point/Melting range: Not determined.
Boiling point/Boiling range: 100 °C (212 °F)

· Flash point: None

Flammability (solid, gaseous): Not applicable.
 Ignition temperature: 240 °C (464 °F)
 Decomposition temperature: Not determined.

· **Auto igniting:** Product is not self-igniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.

• **Vapor pressure @ 20 °C (68 °F):** 23 hPa (17 mm Hg)

• **Density** @ **20** °**C** (**68** °**F**): 1.18 g/cm³ (9.847 lbs/gal)

Relative density: Not determined.
 Vapor density: Not determined.
 Evaporation rate: Not determined.

· Solubility in / Miscibility with:

Water: Fully miscible.

• Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic @ **20** °**C** (**68** °**F**): 50 mPas

Kinematic: Not determined.

· Solvent content:

 Organic solvents:
 6.0 %

 Water:
 66.4 %

 VOC content:
 6.0 %

 Solids content:
 7.3 %

· Other information: No further relevant information available.

10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

1.5/1.050	-					
· LD/LC50 \	· LD/LC50 values that are relevant for classification:					
111-76-2 E	111-76-2 Ethylene Glycol Monobutyl Ether					
Oral	LD50	470 mg/kg (rat)				
Dermal	LD50	220 mg/kg (rab)				
Inhalative	LC50/4 h	2174.91 mg/l (rat)				
10213-79-	10213-79-3 Sodium Metasilicate Pentahydrate					
Oral	LD50	847 mg/kg (rat)				
1310-73-2	1310-73-2 Sodium Hydroxide					
Oral	LD50	2000 mg/kg (rat)				
60-00-4 E	60-00-4 Edetic acid					
Oral	LD50	4500 mg/kg (rat)				

- · Primary irritant effect:
- On the skin: Strong caustic effect on skin and mucous membranes.
- · On the eye:

Strong irritant with the danger of severe eye injury.

Corrosive effect.

Causes serious eye irritation.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

. Harmful

Corrosive

Irritant

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer):			
111-76-2 Ethylene Glycol Monobutyl Ether	3		
· NTP (National Toxicology Program):			
None of the ingredients are listed.			
· OSHA-Ca (Occupational Safety & Health Administration):			
None of the ingredients are listed.			

US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

12 Ecological Information

· Toxicity:

· Aquatic toxicity:

111-76-2 Ethylene Glycol Monobutyl Ether

EC50 1815 mg/l (Water flea)

1310-73-2 Sodium Hydroxide

EC50 40 mg/l (daphnia)

- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Additional ecological information:
- · General notes:

Generally not hazardous for water.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport Information

· UN-Number:

· **DOT, ADR, IMDG, IATA** UN1760

· UN proper shipping name:

· **DOT** Corrosive liquids, n.o.s. (Sodium Hydroxide)

ADR
 UN1760 Corrosive liquids, n.o.s. (Sodium Hydroxide)
 IMDG, IATA
 UN1760 Corrosive liquids, n.o.s. (Sodium Hydroxide)

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

· Transport hazard class(es):

· DOT



· Class: 8 Corrosive substances

· Label:

· ADR



· Class: 8 (C9) Corrosive substances

· Label:

· IMDG, IATA



· Class: 8 Corrosive substances

· Label: 8

· Packing group:

· DOT, ADR, IMDG, IATA ///

· Environmental hazards: Not applicable.

· Special precautions for user: Warning: Corrosive substances

Danger code (Kemler):
EMS Number:
Segregation groups:
Stowage Category

80
F-A,S-B
Alkalis
B

Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations:** On passenger aircraft/rail: 1 L

On cargo aircraft only: 30 L

· ADR

· Excepted quantities (EQ): Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

· IMDG

· Limited quantities (LQ): 1L

· Excepted quantities (EQ): Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1760 CORROSIVE LIQUIDS, N.O.S. (SODIUM

HYDROXIDE), 8, III

15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- · SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 Ethylene Glycol Monobutyl Ether

· TSCA (Toxic Substances Control Act):

25155-30-0 Sodium dodecylbenzenesulphonate

111-76-2 Ethylene Glycol Monobutyl Ether

ANIONIC SURFACTANT

1310-73-2 Sodium Hydroxide

60-00-4 Edetic acid

7732-18-5 Water, distilled water, deionized water

- · California Proposition 65:
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· New Jersey Right-to-Know List:

25155-30-0 Sodium dodecylbenzenesulphonate

111-76-2 Ethylene Glycol Monobutyl Ether

1310-73-2 Sodium Hydroxide

60-00-4 Edetic acid

· New Jersey Special Hazardous Substance List:

111-76-2 Ethylene Glycol Monobutyl Ether CA, F2 1310-73-2 Sodium Hydroxide CO, R1

(Contd. on page 11)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

· Pennsylva	nia Right-to-Know List:	
111-76-2	Ethylene Glycol Monobutyl Ether	
1310-73-2	Sodium Hydroxide	
60-00-4	Edetic acid	
· Pennsylva	nia Special Hazardous Substance List:	
1310-73-2	Sodium Hydroxide	E
60-00-4	Edetic acid	E

· Carcinogenic categories:

· EPA (Environmental Protection Agency):	
111-76-2 Ethylene Glycol Monobutyl Ether	NL NL
· TLV (Threshold Limit Value established by ACGIH):	
111-76-2 Ethylene Glycol Monobutyl Ether	A3
· NIOSH-Ca (National Institute for Occupational Safety and Health):	
None of the ingredients are listed.	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS05

· Signal word: Danger

Hazard-determining components of labeling:

Sodium Metasilicate Pentahydrate

Sodium Hydroxide

· Hazard statements:

H314 Causes severe skin burns and eye damage.

· Precautionary statements:

P260 Do not breathe dusts or mists.
P280 Wear eye protection / face protection.
P264 Wash thoroughly after handling.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data

Sheet).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P405 Store locked up.

(Contd. on page 12)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/20/2016 Reviewed on 05/20/2016

Trade name: Truck Wash Plus

P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 05/20/2016 / 3

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Lig. 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

· * Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106