

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

1 Identification

- · Product identifier
- · Trade name: WAM-O Aluminum Brightener (WAMO Plus)
- · Product number: ngt-wamo
- · Relevant identified uses of the substance or mixture and uses advised against
- · Product description PC35 Washing and cleaning products (including solvent based products)
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

NuGeneration Technologies, LLC (dba NuGenTec)

1155 Park Avenue, Emeryville, CA 94608

salesteam@nugentec.com

www.nugentec.com

1-888-996-8436 or 1-707-820-4080 for product information • Emergency telephone number:

PERS Emergency Response: Domestic and Canada - 1-800-633-8253, International 1-801-629-0667

2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 2 H310 Fatal in contact with skin.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS05 GHS06 GHS08

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

· Signal word Danger

Hazard-determining components of labeling:

hydrofluoric acid

sulfuric acid

· Hazard statements

Harmful if swallowed.

Fatal in contact with skin.

Causes severe skin burns and eye damage.

May cause cancer.

· Precautionary statements

Do not breathe dusts or mists.

Wear protective gloves / protective clothing.

Wear eye protection / face protection.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

If swallowed: Call a poison center/doctor if you feel unwell.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin: Wash with plenty of water.

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 4 Fire = 0

Reactivity = 0

· Hazard(s) not otherwise classified (HNOC): None known



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

3 Composition/information on ingredients

7732-18-5 water, distilled water, deionized water

64%

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous Components:				
CAS: 7664-93-9	sulfuric acid & Carc. 1A, H350; � Skin Corr. 1A, H314	20%		
CAS: 7664-39-3 RTECS: MW 7875000	hydrofluoric acid Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330; Skin Corr. 1A, H314	8%		
CAS: 68603-25-8	ethoxylated propoxylated c8-c10 alcohols Skin Irrit. 2, H315; Eye Irrit. 2A, H319	8%		

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed:

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

- · Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:

7664-93-9 sulfuric acid

PEL Long-term value: 1 mg/m³

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

REL Long-term value: 1 mg/m³

TLV Long-term value: 0.2* mg/m³

*as thoracic fraction

7664-39-3 hydrofluoric acid

PEL Long-term value: 3 ppm

as F

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5* mg/m³, 6* ppm

*15-min, as F

TLV Long-term value: 0.41 mg/m³, 0.5 ppm

Ceiling limit value: 1.64 mg/m³, 2 ppm

as F; Skin, BEI

· Ingredients with biological limit values:

7664-39-3 hydrofluoric acid

BEI 3 mg/g creatinine

urine

prior to shift

Fluorides (background, nonspecific)

10 mg/g creatinine

urine

end of shift

Fluorides (background, nonspecific)

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

be checked prior to the application.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Safety glasses

Tightly sealed goggles

0.51						
uun	vereal	ana	chemi	nra	norti	ΔC
9 6 6			GHEITH			53
	,			 7. 7	~~.~	\sim

mile in a second control of the second contr	ioui uiiu oiioiiiioui piopoi aoo
· General Information	
· Appearance:	
Form:	Liquid
A .	O'1 1

Information on basic physical and chemical properties

Color: Colorless
Odor: Mild

· Odor threshold: Not determined.

· pH-value @ 20 °C (68 °F):

· Change in condition

Melting point/Melting range:Not determined.Boiling point/Boiling range:19 °C (66 °F)

Flash point: Not applicable.
 Flammability (solid, gaseous): Not applicable.

Flammability (solid, gaseous): Not applicable.
 Ignition temperature: 270 °C (518 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

 Lower:
 0.0 Vol %

 Upper:
 0.0 Vol %

• **Vapor pressure @ 20 °C (68 °F):** 23 hPa (17 mm Hg)

• **Density @ 20 °C (68 °F):** 1.088 g/cm³ (9.079 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

· Viscosity:

Dynamic @ 20 °C (68 °F): 3 mPas

Kinematic: Not determined.

· Solvent content:

Organic solvents: 0.0 % Water: 64.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:				
7664-93-9	sulfuric acid				
Oral	LD50 Oral	2140 ml/kg (rat)			
Inhalative	LC50/96 hours	375 mg/l (rat) Sulfuric acid is harmful by all routes of entry.			
7664-39-3	hydrofluoric a	cid			
Oral	LD50	1276 mg/kg (rat)			
	LD50 Oral	80 ml/kg (Guinea Pig)			
Inhalative	LC50/4 h	2240 mg/l (rat)			
68603-25-	8 ethoxylated p	propoxylated c8-c10 alcohols			
Oral	LD50 Oral	3800 ml/kg (rat) The product has a low acute toxicity			
. Primary i	rritant effect				

- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong irritant with the danger of severe eye injury.

Corrosive effect.

Causes serious eve irritation.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

Harmful

Corrosive

Irritant

Very toxic

Danger through skin absorption.

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
7664-93-9 sulfuric acid	1
· NTP (National Toxicology Program)	
7664-93-9 sulfuric acid	K
· OSHA-Ca (Occupational Safety & Health Administration)	

12 Ecological information

None of the ingredients are listed.

· Toxicity

· Aquatic toxicity:

7664-93-9 sulfuric acid

EC50 22 mg/l (daphnia)

7664-39-3 hydrofluoric acid

EC50 270 mg/l (Fathead Minnow)

68603-25-8 ethoxylated propoxylated c8-c10 alcohols

EC50 8.7 mg/l (Trout)

12.61 mg/l (daphnia)

Method: OECD Test Guideline 202

internal evaluation

Harmful to aquatic invertebrates.

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 06/01/2015 Issue date 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

775	_			
<i>11</i> 1	ranc	nort	ıntor	mation
141	папы	DUIL	иич	mauvn

	Ul	N-	Ν	ur	nb	er
--	----	----	---	----	----	----

· DOT, ADR, IMDG, IATA

UN2922

· UN proper shipping name

· DOT

Corrosive liquids, toxic, n.o.s. (Hydrogen fluoride,

Sulfuric acid)

· ADR

UN2922 Corrosive liquids, toxic, n.o.s. (Hydrogen

fluoride, Sulfuric acid)

· IMDG, IATA

CORROSIVE LIQUID, TOXIC, N.O.S. (HYDROGEN

FLUORIDE, SULPHURIC ACID)

- · Transport hazard class(es)
- · DOT





· Class

8 Corrosive substances

8, 6.1

· Label · ADR





· Class · Label 8 (CT1) Corrosive substances

8+6.1

(Contd. on page 10)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

· IMDG · Class 8 Corrosive substances · Label 8/6.1 · IATA · Class 8 Corrosive substances · Label 8 (6.1) · Packing group · DOT, ADR, IMDG, IATA II· Environmental hazards: Not applicable. · Special precautions for user Warning: Corrosive substances Danger code (Kemler): F-A.S-B · EMS Number: Acids · Segregation groups · Transport in bulk according to Annex II of Not applicable. MARPOL73/78 and the IBC Code · Transport/Additional information: · DOT · Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L · ADR · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · IMDG · Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN2922, Corrosive liquids, toxic, n.o.s. (Hydrogen · UN "Model Regulation": fluoride, Sulfuric acid), 8 (6.1), II



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355	(extremel	v hazardous	substances) <i>:</i>
---------------	-----------	-------------	------------	------------

7664-93-9 sulfuric acid

7664-39-3 hydrofluoric acid

· Section 313 (Specific toxic chemical listings):

7664-93-9 sulfuric acid

7664-39-3 hydrofluoric acid

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · California Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

7664-93-9 sulfuric acid

*A*2

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS05 GHS06 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

hydrofluoric acid

sulfuric acid

· Hazard statements

Harmful if swallowed.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

Fatal in contact with skin.

Causes severe skin burns and eye damage.

May cause cancer.

· Precautionary statements

Do not breathe dusts or mists.

Wear protective gloves / protective clothing.

Wear eye protection / face protection.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

If swallowed: Call a poison center/doctor if you feel unwell.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin: Wash with plenty of water.

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· State Right to Know		
CAS: 7732-18-5	water, distilled water, deionized water	64%
CAS: 7664-93-9	sulfuric acid	20%
	🕸 Carc. 1A, H350; < Skin Corr. 1A, H314	
CAS: 68603-25-8	ethoxylated propoxylated c8-c10 alcohols	8%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
CAS: 7664-39-3	hydrofluoric acid	8%
RTECS: MW 7875000	♦ Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330; ♦ Skin Corr. 1A, H314	
All ingredients are liste	<u>d</u> .	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2015 Reviewed on 06/01/2015

Trade name: WAM-O Aluminum Brightener (WAMO Plus)

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision 06/01/2015 / 2

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 2: Acute toxicity, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Acute Tox. 1: Acute toxicity, Hazard Category 1

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Carc. 1A: Carcinogenicity, Hazard Category 1A

· * Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106