NugenTec High Performance Materials Tech

METALWORKING FLUIDS

Technical Data Sheet

100325

METALWORKING FLUIDS - SYNTHETICS

NuKut: 100% Synthetic Fluids for a variety of metalworking applications

Applications: NuGeneration Technologies' **NuKut** lines of synthetic metalworking fluids are liquid <u>Oll-FREE</u> products designed to assist in many metal cutting and machining operations on ferrous, non-ferrous, and specialty alloys including aluminum. 100% non-hazardous, non-chlorine, non-sulfur, non-phenol and non-nitrate based fluids with propriety extreme pressure lubricants are easily disposed of. **NuKut LT 1** is also specifically designed for use in diamond wheel grinding of carbide and diamond (PCD) tool inserts. Providing excellent surface finishes while <u>extending stone life</u>. Prevents Carbide Leaching.

NuKut MD 1 is specifically designed for use CNC machining centers. **NuKut MD 1** increases tool life, sump life, improves cutting speeds and prevents corrosion. Replace soluble oils in your shop with NuKut MD 1. Eliminate the hazardous associated with oils; like disposal, fire, dermatitis & skin sensitization. NuKut MD 1 provides a non-hazardous easily removed corrosion resistant coating on all metals.



Benefits:

- Low foaming
- High lubricity
- Excellent surface finishes
- Hard water stable

- Improved sump life
- Improved tool life
- Excellent corrosion protection
- Easily disposed of

- Operator friendly
- Mild odor
- Prevent carbide leaching
- · Easy to clean off

Typical Usage Parameters:

| | NuKut MD 1 | NuKut LT 1 | Bug Sticks |
|----------------------------|---------------|------------|---------------------------|
| Description | CNC Machining | Grinding | Bacterial & Fungal Checks |
| Grinding | 2 – 4% | 2 - 10% | Easy to use |
| Cutoff and Sawing | 5 - 15% | 10% | Just dip in & |
| Milling, Drilling, Turning | 5 - 10% | | Results 1 day |

Physical Properties:

| | NuKut MD 1 | NuKut LT 1 | Bug Sticks |
|-------------------------|------------|-------------|-------------|
| pH, concentrate & pH 5% | 9.8 / 9.5 | 10.6 / 10.4 | |
| Bulk Density, #/gal | 8.5 | 8.6 | Regular use |
| Chelates | None | None | An early |
| Solubility in water | Complete | Complete | Warning |
| Biodegradable | Yes | Yes | Against |
| Nitrites/nitrates | No | No | Microbial |
| Oil containing fluid | Oil Free | Oil Free | Spoilage |
| Cast Iron Chip Test | 3% | N/A | |

COOLANT MANAGEMENT: Send any NuGenTec Coolant from your sump into our lab for a <u>FREE analysis</u>. Consisting of: actual concentration, pH, Conductivity (TDS), Bacterial counts, % emulsified oil & total oil. Receive recommendations on sump life extension and coolant maintenance.